

Tender specification

Electrode steam humidifier **StandardLine E**

Ready for connection compact steam humidifier system for fully automatic and intrinsically safe generation of mineral-free, odourless and sterile steam. Steam output 5 – 65 kg/h per individual device. Installation and maintenance friendly design, for wall mounting. Easy to mount with all commercially available mounting rail systems, manufacturer-specific systems are not required. Corrosion-protected housing completely powder coated, stainless steel housing trough with separate areas for steam generation and electrics. With VDE and GS certification mark, CE and EAC compliant. Developed and manufactured in Germany. For direct connection to all standard tap water mains. No water treatment necessary.

Standard equipment scope:

- Separable plastic cylinder - durable, easily cleaned without chemicals and reusable
- Massive large area stainless steel electrodes – especially long service life, replaced quickly and without tools
- Integrated circuit breaker
- Powerful blow-down pump to extend the service life by pumping out hardeners
- Steam hose adapter for fast installation and removal of the cylinder
- Device components easily accessed from three sides with removable device cover
- Assembly material.

Powerful control electronics for fastest possible steam delivery with optimal energy utilisation and low maintenance operating mode. Comprehensive operational reliability through continuous self-monitoring of all device functions. The control processes all established control signals.

Performance characteristics:

- Automatic system test incl. self-diagnosis checking all functions and device components
- Continuous or 1-step control selectable
- Integrated PI controller
- Display
- 4 function keys
- 10 symbols for displaying operating and service messages
- 2 potential-free remote signals, one of them freely programmable from 15 options
- Stand-by blow-down to prevent stationary cylinder water according to VDI 6022
- DVGW compliant flushing of dead-end line to prevent tap water stagnation
- Self-adaption to the respective water quality
- Integrated communication protocol Modbus RTU
- Integrated galvanically insulated serial interface / RS-485 (/ EIA-485)
- Switch between the operating modes "energy-optimised", "load-optimised" and separate inputs for voltage, current and resistance signals
- Analogue output 0-10 V for simultaneous use of several devices

Please select option:

- Cylinder flushing system for significant extension of the service lives of cylinders by means of increased discharging of screenable scale deposits or hardeners
- Preventive device type AB in accordance with DIN EN 1717 for potable water protection, allows a local backflow preventer to be dispensed with

- Galvanised electrodes for optimised service lives of electrodes with high chloride content of the feed water
- Integrated waste water cooling to limit waste water temperature to max. 60 °C, when using PVC waste water pipes or pumping equipment
- Up to 2 additional relais signal functions, freely parametrisable from 15 functions, for optimum integration in superordinate building technology
- With stainless steel housing – completely made of brushed stainless steel for SLE05 – SLE30
- External 3.5" touch display as surface-mounted version in its own housing

Technical specifications:

Steam output	kg/h (max.)
Electrical connection / /	V / phases / (N)
Nominal power rating	kW (max.)
Nominal current	A (max.)
Control voltage	230V / N 50-60Hz separately	
Make	HygroMatik	
Type	StandardLine E	

Accessories

- Stainless steel steam manifold with condensate recirculation

Quantity	
Diameter	(25 or 40 mm)
Length	(220, 400, 600, 900, 1200 or 1450 mm)

- Steam hose

Diameter	(25 or 40 mm)
Length	

- Condensate hose

Length
--------	-------

- Water drain hose

Length
--------	-------