

Technical Data CompactLine

Type	C01	C02	C06	C10	C17	C22	C30	C45	C58
Steam output [kg/h]	1	2	6	10	17	22	30	45	58
Electrical supply	230V/1/N 50-60Hz		400V/3/N 50-60Hz*						
Electrical power [kW]	0.75	1.5	4.5	7.5	12.8	16.5	22.5	33.8	43.5
Current [A]	3.3	6.5	6.5	10.8	18.4	23.8	32.5	48.8	62.8
Fuse [A]	1x6	1x10	3x10	3x16	3x20	3x35	3x35	3x63	3x63
Control	Basic, Comfort				Basic, Comfort and Comfort Plus				
Control voltage [V]	230V								
Steam hose connection [mm]	1x25				1x40		1x40**	2x40	
Empty weight [kg]	8,5	10	10	12	19	19	20	22	31
Operational weight [kg]	9,8	12,6	13	18	37	37	38	49	77
Height [mm]	385	365	436	478	651	651	651	707	787
Width [mm]	355	392	403	412	480	480	480	528	615
Depth [mm]	171	221	208	228	308	308	308	343	394
Water supply	1-10 bar, with connection 3/4"								

* Other voltages on request

** Inclusive Y-piece for connection of two manifolds

*** Inclusive T-pieces for condensate return from both manifolds

Subject to technical amendments without notice

Our Service for you

- HygroMatik distributors in more than 35 countries worldwide
- Technical hotline +49 4193 859 - 293 or hotline@hygromatik.com
- Manuals, planing tools and workshop offers are available online at www.hygromatik.com



HYGROMATIK[®]
WE HUMIDIFY THE AIR

HygroMatik GmbH
Lise-Meitner-Str. 3
24558 Henstedt-Ulzburg
Germany

T +49 4193 895-0
F +49 4193 895-33
hy@hygromatik.de
www.hygromatik.com

A Member of the **spirax**/**sarco** group