



Centrifugal Atomiser DG

for direct room humidification

Mount the HygroMatik Atomiser DG for direct room humidification directly on production hall or storage room ceilings. It generates a fine water mist and its powerful integrated fan distributes this evenly to the ambient air. This creates an additional cooling effect. The DG has a very low energy consumption and works without water losses.



- Humidification capacity 4 and 8 l/h
- Operates with fresh water, therefore no water losses
- · Additional cooling effect
- Very low electrical energy consumption
- Simple and quick maintenance
- Full 360° degree humidification



Direct room humidification



Technical Data for Centrifugal Atomiser DG

Type DG4 DG8 Humidification capacity [kg/h] 4 8 Effective volume ** [m³] 400 1200 Circulation air [m³/h] 350 600 Motor power rate [kW] 0.14 0.16 Electrical supply * 230V/50 Hz/1N 400 V/50 Hz/3N Nominal current [A] 0.65 0.58 Diameter [mm] 450 620 Height [mm] 280 390 Water supply Feed [bar] 1-6 1-10 R 1/4" R 1/4" R 1/4" Safety overflow R 1/2" R 1/2" Empty weight [kg] 4.5 15			
Effective volume ** [m³] 400 1200 Circulation air [m³/h] 350 600 Motor power rate [kW] 0.14 0.16 Electrical supply * 230V/50 Hz/1N 400 V/50 Hz/3N Nominal current [A] 0.65 0.58 Diameter [mm] 450 620 Height [mm] 280 390 Water supply Feed [bar] 1-6 1-10 R 1/4" R 1/4" R 1/4" Safety overflow R 1/2" R 1/2"	Туре	DG4	DG8
Circulation air [m³/h] 350 600 Motor power rate [kW] 0.14 0.16 Electrical supply * 230V/50 Hz/1N 400 V/50 Hz/3N 0.65 0.58 Diameter [mm] 450 620 Height [mm] 280 390 Water supply Feed [bar] 1-6 1-10 R 1/4" R 1/4" Safety overflow R 1/2" R 1/2"	Humidification capacity [kg/h]	4	8
Motor power rate [kW] 0.14 0.16 Electrical supply * 230V/50 Hz/1N 400 V/50 Hz/3N 0.65 0.58 Diameter [mm] 450 620 Height [mm] 280 390 Water supply Feed [bar] 1-6 1-10 R 1/4" R 1/4" Safety overflow R 1/2" R 1/2"	Effective volume ** [m ³]	400	1200
Electrical supply * 230V/50 Hz/1N 400 V/50 Hz/3N 0.65 0.58 Diameter [mm] 450 620 Height [mm] 280 390 Water supply Feed [bar] 1-6 1-10 R 1/4" R 1/4" Safety overflow R 1/2" R 1/2"	Circulation air [m³/h]	350	600
Nominal current [A] 0.65 0.58	Motor power rate [kW]	0.14	0.16
Height [mm] 280 390 Water supply Feed [bar] 1-6 1-10 R 1/4" R 1/4" Safety overflow R 1/2" R 1/2"	* * *		
Water supply Feed [bar] R 1/4" Safety overflow R 1/2" R 1/2"	Diameter [mm]	450	620
Feed [bar] 1-6 1-10 R 1/4" R 1/4" Safety overflow R 1/2" R 1/2"	Height [mm]	280	390
Empty weight [kg] 4.5 15	Feed [bar]	R 1/4"	R 1/4"
	Empty weight [kg]	4.5	15
Operational weight [kg] 5 15.5	Operational weight [kg]	5	15.5

- * Other voltages on request.
- ** Varies depending on room temperature and required room humidity.

Subject to technical amendments without notice.



HygroMatik GmbH Lise-Meitner-Str. 3 24558 Henstedt-Ulzburg hy@hygromatik.de Germany

T +49 4193 895-0 F +49 4193 895-33 www.hygromatik.com

member of **CAREL group**

