

Technical Data HeaterLine

Type	HL06	HL09	HL12	HL18	HL24	HL27	HL30	HL36	HL45	HL60 2x HL30	HL70 2x HL36	HL80 HL36+HL45	HL90 2x HL45
Steamoutput [kg/h]	6	9	12	18	24	27	30	36	45	60	72	81	90
Number of units	1									2			
Electrical supply / unit	400V/3/N 50-60Hz*												
Power rating / unit [kW]	4.5	6.8	9	13.5	18	20.3	22.5	27	33.8	22.5	27	33.8	33.8
Input / unit [A]	11.3	16.9	19.5	29.3	39	29.3	39	58.5	58.5	39	58.5	58.5	58.5
Circuit protection / unit [A]	3x16	3x20	3x20	3x35	3x40	3x35	3x40	3x63	3x63	3x40	3x63	3x63	3x63
Control / unit	Basic, Comfort, ComfortPlus or Professional									Basic, Comfort and ComfortPlus			
Number of heater elements / unit	1	2	2	4	3	5	4	5	4	4	1x4, 1x5	5	
Steam hose connection / unit [mm]	1x25**			1x40				2x40, Y-piece incl.		2x40, Y-piece incl.			
Empty weight [kg]	36	37	38	40	48	49	94	95	96	97			
Operation weight [kg]	51	52	53	55	78	79	154	155	156	157			
Height [mm]	830						855						
Width [mm] / unit	645						688						
Depth [mm]	325						395						
Water supply***	Fully demineralised water / cleaned condensate / partially softened and standard tap water, 1-10 bar, 13 mm hose												
Fan unit, wall mounted	VG08	VG17	VG30				2x VG30		4x VG30				
Air circulation of fan unit [m³/h]	160	185	350				2x350		4x350				

* Other voltages upon request

** Reducing piece DN40 to DN25 included

*** For very hard feedwater a water analysis is necessary

Subject to technical amendments without notice

Our Service for you

- HygroMatik distributors in more than 35 countries worldwide
- Technical hotline +49 4193 859 - 293 or hotline@hygromatik.com
- Manuals, planing tools and workshop offers are available online at www.hygromatik.com



HYGROMATIK[®]
WE HUMIDIFY THE AIR

HygroMatik GmbH T +49 4193 895-0
Lise-Meitner-Str. 3 F +49 4193 895-33
24558 Henstedt-Ulzburg hy@hygromatik.de
Germany www.hygromatik.com

A Member of the **spirax**/**sarco** group