

Technical Data HyLine

Type	Hy05	Hy08	Hy13	Hy17	Hy23	Hy30	Hy45	Hy60	Hy90	Hy116
Steam output [kg/h]	5	8	13	17	23	30	45	60	90	116
Electrical supply*	400V/3/N 50-60Hz*									
Electrical power [kW]	3.8	6	9.8	12.8	17.3	22.5	33.8	2x22.5	2x33.8	2x43.5
Current [A]	5.4	8.7	14.1	18.4	24.9	32.5	48.8	2x32.5	2x48.8	2x62.8
Fuse [A]	3x6	3x10	3x16	3x20	3x35	3x35	3x63	6x35	6x63	6x63
Control	Basic, Comfort		Basic, Comfort and ComfortPlus							
Control voltage [V]	230									
Steam hose connection	1x25 mm			1x40 mm		2x40 mm		4x40mm		
Empty weight [kg]	13	13	20	20	22	28	39	47	70	70
Operational weight [kg]	19	19	38	38	40	55	85	101	162	162
Height [mm]	480	480	651	651	651	708	788	709	788	788
Width [mm]	449	449	522	522	522	561	654	927	1061	1061
Depth [mm]	251	251	301	301	301	344	403	334	403	403
Water supply	1-10 bar, with connection 3/4"									
Fan unit, wall mounted	1x VG08	1x VG08	1x VG17	1x VG17	1x VG30	1x VG30	2x VG30	2x VG30	4x VG30	4x VG30

* Other voltages on request
Subject to technical amendments without notice

Our Service for you

- HygroMatik distributors in more than 35 countries worldwide
- Technical hotline +49 4193 859 - 293 or hotline@hygromatik.com
- Manuals, planing tools and workshop offers are available online at www.hygromatik.com



HYGROMATIK[®]
WE HUMIDIFY THE AIR

HygroMatik GmbH T +49 4193 895-0
Lise-Meitner-Str. 3 F +49 4193 895-33
24558 Henstedt-Ulzburg hy@hygromatik.de
Germany www.hygromatik.com

A Member of the **spirax**/**sarco** group