



Technical data for StandardLine (heater elements)

A higher humidification performance is possible by connecting units together.

Electrical supply *	Type	SLH03	SLH06	SLH09	SLH015	SLH25	SLH40	SLH50
208-240 VAC / 1 / N / 50-60Hz	Steam output [kg/h]	2.5-3.3	4.9-6.5					
	Steam output [lbs/h]	5.5-7.3	10.8-14.3					
	Rated power [kW]	1.8-2.4	3.7-4.9					
	Rated current [A]	8.8-10.2	17.7-20.4					
208-240 VAC / 3 / 50-60Hz	Steam output [kg/h]	2.5-3.3	4.9-6.5		12.4-16.6			
	Steam output [lbs/h]	5.5-7.3	10.8-14.3		27.3-36.6			
	Rated power [kW]	1.8-2.4	3.7-4.9		9.3-12.4			
	Rated current [A]	8.8-10.2	17.7-20.4		25.9-29.9			
440-480 VAC / 3 / 50-60Hz	Steam output [kg/h]		5.5-6.5	8.2-9.8	13.9-16.6	23.0-27.4	37.0-44.0	43.7-52.0
	Steam output [lbs/h]		12.1-14.3	18.1-21.6	30.6-36.6	50.9-60.4	81.6-97.0	96.3-114.6
	Rated power [kW]		4.1-4.9	6.2-7.3	10.4-12.4	17.3-20.6	27.7-33.0	32.8-39.0
	Rated current [A]		9.4-10.2	14.0-15.3	13.7-14.9	22.7-24.8	36.4-39.7	43.0-46.9
Number of cylinders	1							
Control type	LED display							
Internal control voltage	208-240V / 1 / N / 50-60Hz							
Steam hose connection [mm]	1 x DN 25 ID			1 x DN 40 ID		2 x DN 40 ID		
Steam hose connection [in]	1 x 1 ID			1 x 1.6 ID		2 x 1.6 ID		
Dimensions **								
Height [mm/in]	570/22.4			730/28.7		820/32.3		
Width [mm/in]	350/13.8			425/16.7		590/23.2		
Depth [mm/in]	245/9.6			320/12.6		415/16.3		
Water installation	Fully demineralized water / cleaned condensate: 1-10 bar / 14.5-145 PSI, with 3/4" connection Partially softened water / tap water of varying qualities: 1-10 bar / 14.5-145 PSI, for 3/4" external thread							

Subject to technical changes.

* Other voltages upon request.

** Outer width and depth dimensions.
Height including outlet connection.



HygroMATIK®

member of CAREL group 

HygroMatik GmbH
Lise-Meitner-Str. 3
24558 Henstedt-Ulzburg
Germany

T +49 4193 895-231
F +49 4193 895-33
axel.zadina@hygromatik.de
www.hygromatik.com

HygroMatik USA
PO Box 10084
Lancaster, PA 17605
USA

T 717 299 5679
F 717 299 5679
info@hygromatikusa.com
www.hygromatik.com