

Technical Data MiniSteam E (electrodes)

Electrical supply	Type	MSE05	MSE10
208-240 VAC / 1 / N / 50-60 Hz	Steam output [lb/h]	9.3 - 10.6	
	Steam output [kg/h]	4.2 - 4.8	
	Rated power input [kW]	3.1 - 3.6	
	Rated current [A]	15	
	Circuit protection [A] ⁽¹⁾	1 x 20	
208-240 VAC / 3 / 50-60 Hz	Steam output [lb/h]	9.9 - 11.4	15.9 - 18.3
	Steam output [kg/h]	4.5 - 5.2	7.2 - 8.3
	Rated power input [kW]	3.4 - 3.9	5.4 - 6.2
	Rated current [A]	9.4	15
	Circuit protection [A] ⁽¹⁾	3 x 15	3 x 15
440-480 VAC / 3 / 50-60 Hz	Steam output [lb/h]	10.6 - 11.5	21.2 - 23.0
	Steam output [kg/h]	4.8 - 5.2	9.6 - 10.4
	Rated power input [kW]	3.6 - 3.9	7.2 - 7.8
	Rated current [A]	4.7	9.4
	Circuit protection [A] ⁽¹⁾	3 x 10	3 x 10
Empty weight [kg/lb]		15 / 33	
Operational weight [kg/lb]		20 / 44	
Dimensions W x H x D ⁽²⁾ [inch]		15.4 x 23.4 x 10.0	
Water installation		Tap water of varying qualities 1 to 10 bar / 14.5 - 145 PSI, with 3/4" connection	

Subject to technical changes.

⁽¹⁾ Multiply power input by 1.1 after full blowdown. Consider overload capacity of automatic breakers.
If necessary, select the next higher rating.

⁽²⁾ Outer dimensions of width and depth. Height incl. drain connection.

Our service for you

- HygroMatik distributors in more than 45 countries worldwide
- Technical hotline +49 4193 859 - 293 or hotline@hygromatik.com
- Manuals, planning tools and workshop offers are available online at www.hygromatik.com



HygroMatik GmbH
Lise-Meitner-Str. 3
24558 Henstedt-Ulzburg
Germany

T +49 4193 895-231
hy@hygromatik.de
www.hygromatik.com

HygroMatik USA
PO Box 10084
Lancaster, PA 17605
USA

T 717 299 5679
hy@hygromatik.com
www.hygromatik.com